


PERKO®

Cat. No. 1607 Series White All-Round Lights



The above lights are designed for use on power driven vessels under 20 meters (65.6 ft.) in length operating on a nominal 12 volt system. In order to comply with '72 COLREGS and the U.S. Inland Rules, the following must be adhered to:

MOUNTING INFORMATION

Read all instructions before proceeding.

- 1). For proper light selection, positioning and configuration, refer to A.B.Y.C. Standard A-16*, the '72 COLREGS*, and the U.S. Inland Rules*.
- 2). These lights are designed to be mounted on horizontal tubing or rails 3/4" to 1-1/2" diameter.
- 3). Horizontal rotation of these lights is unimportant, as all-round lights have 360° horizontal arc of visibility.
- 4). Using the base or the plastic mounting insulator as a template, place it on the mounting surface such that the globe can be adjusted to a vertical position when mounted.
- 5). Drill mounting holes for #8 round or panhead screws (Not Supplied).
- 6). Attach supply connections to the light, making sure to wire in accordance with both A.B.Y.C. Standard E-9* and U.S. Coast Guard Safety Standards for Boat Electrical Systems (33 CFR 183)*.
- 7). Mount the light. A self adhesive insert is provided to securely mount the light to 1-1/4" and 1-1/2" rails.
- 8). Adjust pole such that the globe is in a vertical position during operation, in order to assure compliance with the technical details of the regulations and employ the "Reduced Glare" feature.
- 9). Relamp only with bulb type as marked on globe or inside fixture. Use ANSI #906 bulbs (PERKO Cat. No. 0338DP2CLR 12V, 9W).

*The above referenced standards can be obtained from:

- | | |
|---|--|
| (1). American Boat & Yacht Council, Inc.
613 Third Street, Suite 10
Annapolis, MD 21403 | (2). U.S. Coast Guard
Washington, D.C. 20593
(or your local C.G. Office) |
|---|--|



12/08
1607INS1

PERKO, INC.
16490 N.W. 13th Avenue
Miami, FL 33169-5707
www.perko.com